

Cylinder Technical Information

Please note: cylinder height and diameter are only approx. - may vary slightly.

| Gas | Range | Pressure | Volume | Capacity | Cylinder Outlet | Height | Diameter |
|----------------------------|----------|-----------------------|--------------------|------------|-------------------------|---------|----------|
| Hobbyweld 5 | Original | 137 bar (1987 psi) | 1.34m ³ | 9 litre | 5/8" BSP RH Female | 840 mm | 160 mm |
| | Plus | 230 bar (3335 psi) | 4.86m ³ | 20 litre | 5/8" BSP RH Female | 950 mm | 200 mm |
| | Ultra | 300 bar (4531 psi) | 6.13m ³ | 20 litre | EN 561 Quick-Action | 1050 mm | 200 mm |
| Hobbyweld 15 | Original | 137 bar (1987 psi) | 1.40m ³ | 9 litre | 5/8" BSP RH Female | 840 mm | 160 mm |
| | Plus | 230 bar (3335 psi) | 5.09m ³ | 20 litre | 5/8" BSP RH Female | 950 mm | 200 mm |
| | Ultra | 300 bar (4531 psi) | 6.46m ³ | 20 litre | EN 561 Quick-Action | 1050 mm | 200 mm |
| Argon | Original | 137 bar (1987 psi) | 1.32m ³ | 9 litre | 5/8" BSP RH Female | 840 mm | 160 mm |
| | Plus | 230 bar (3335 psi) | 4.78m ³ | 20 litre | 5/8" BSP RH Female | 950 mm | 200 mm |
| | Ultra | 300 bar (4531 psi) | 6.06m ³ | 20 litre | EN 561 Quick-Action | 1050 mm | 200 mm |
| Oxygen | Original | 137 bar (1987 psi) | 1.33m ³ | 9 litre | 5/8" BSP RH Female | 840 mm | 160 mm |
| | Plus | 230 bar (3335 psi) | 4.82m ³ | 20 litre | 5/8" BSP RH Female | 950 mm | 200 mm |
| | Ultra | 230 bar (3335 psi) | 4.82m ³ | 20 litre | EN 561 Quick-Action | 1050 mm | 200 mm |
| Acetylene | Original | - | 0.88m ³ | 5 litre | 5/8" BSP LH Female | 550 mm | 160 mm |
| | Plus | - | 1.77m ³ | 10 litre | 5/8" BSP LH Female | 760 mm | 160 mm |
| | Ultra | - | 2.55m ³ | 15.9 litre | EN 561 Quick-Action | 880 mm | 200 mm |
| Nitrogen | Original | 137 bar (1987 psi) | 1.32m ³ | 9 litre | 5/8" BSP RH Female | 840 mm | 160 mm |
| | Plus | 230 bar (3335 psi) | 4.25m ³ | 20 litre | 5/8" BSP RH Female | 950 mm | 200 mm |
| Helium | Original | 137 bar (1987 psi) | 1.20m ³ | 9 litre | 5/8" BSP RH Female | 840 mm | 160 mm |
| | Plus | 230 bar (3335 psi) | 3.64m ³ | 20 litre | 5/8" BSP RH Female | 950 mm | 200 mm |
| Carbon Dioxide (IG) | Original | - | 3.21m ³ | 6 kg | 0.860" x 14 TPI RH Male | 840 mm | 160 mm |
| Carbon Dioxide (FG) | Original | - | 3.21m ³ | 6 kg | 0.860" x 14 TPI RH Male | 840 mm | 160 mm |