

Version: **2.2**
Revision Date: **18.10.2020**
Supersedes Version: **2.1**

MSDS Number: **30000000002**
Print Date: **08.10.2021**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier: Acetylene
CAS No.: 74-86-2
Chemical formula: C₂H₂
Synonyms: Acetylene (dissolved), Ethyne, welding gas
REACH Registration Number: 01-2119457406-36

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/
mixture: Industrial and professional use. Perform risk assessment prior to use.
Restrictions on use: None.

1.3 Details of the supplier of the safety data sheet

Address: Dixons Gas Limited
Newbiggin Lane
Westerhope
Tyne and Wear
NE5 1LX
Email address: Orders@dixonsgas.co.uk
Telephone: +44 (0)191 271 4888

1.4 Emergency contact details

Telephone: +44 (0)191 271 4888
Only available on weekdays during the hours of 08:00 to 17:00.
NHS call 111 for free from a landline or mobile.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flammable gases: Category 1A H220: Extremely flammable gas.
Chemically unstable gases: Category A H230: May react explosively even in the absence of air.
Gases under pressure: Dissolved gas H280: Contains gas under pressure; may explode if heated.

2.2 Label elements

Hazard pictograms/symbols:



Signal word: Danger

Hazard statements: H220: Extremely flammable gas.
H230: May react explosively even in the absence of air.
H280: Contains gas under pressure; may explode if heated.

Precautionary statements

Prevention: P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response: P377: Leaking gas fire - do not extinguish, unless leak can be stopped safely.
P381: In case of leakage, eliminate all ignition sources.

Storage: P403: Store in a well ventilated place.

2.3 Other hazards:

High pressure gas.
Can cause rapid suffocation.
Extremely flammable.
May form explosive mixtures in air.
Immediate fire and explosion hazard exists when mixed with air at concentrations exceeding the lower flammability limit (LFL).
High concentrations that can cause rapid suffocation are within the flammable range and should not be entered.
Avoid breathing gas.
Self-contained breathing apparatus (SCBA) may be required.
Substance does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

Environmental effects: Not harmful.

SECTION 3: Composition/information on ingredients

3.1 Substances

Components	EINECS/ELINCS No.	CAS No.	Concentration (Volume)
Acetylene	200-816-9	74-86-2	100%

Components	Classification (CLP)	REACH Reg. #
Acetylene	Flam. Gas 1A; H220 Chem. Unst. Gas A; H230 Press. Gas (Diss.); H280	01-2119457406-36

Refer to section 16 for full text of each relevant hazard statement (H).

Concentration is nominal. For the exact product composition, please refer to technical specifications. For safety reasons, the acetylene is dissolved in acetone (Flam. Liq. 2, Eye Irrit. 2, STOT SE 3) or dimethylformamide (Flam. Liq. 3, Repr. 1B, Acute Tox. 4, Eye Irrit. 2) in the gas receptacle. Vapour of the solvent is carried away as impurity when the acetylene is extracted from the gas receptacle. The concentration of the solvent vapour in the gas is lower than the concentration limits to change the classification of the acetylene. Dimethylformamide is listed in Annex XVII of REACH, and is subject to restrictions on its use. The applicable information from the exposure scenarios for this product are contained in the main body of the MSDS.

3.2 Mixtures

Not applicable

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice: Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact:	In case of direct contact with eyes, seek medical advice.
Skin contact:	Adverse effects not expected from this product. IF exposed or concerned: Get medical advice/attention.
Ingestion:	Ingestion is not considered a potential route of exposure.
Inhalation:	In case of shortness of breath, give oxygen. Move to fresh air. If breathing has stopped or is laboured, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms:	Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.
-----------	--

4.3 Indication of any immediate medical attention and special treatment needed

Treatment:	If exposed or concerned: Get medical attention/advice.
------------	--

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Water spray or fog. Dry powder. Shutting off the source of the gas is the preferred method of control. Be aware of the risk of formation of static electricity with the use of CO2 extinguishers and do not use them in places where a flammable atmosphere may be present.

Extinguishing media which must not be used for safety reasons: Do not use water jet to extinguish.

5.2 Special hazards arising from the substance or mixture:

Incomplete combustion may form carbon monoxide. Upon exposure to intense heat or flame, cylinder will vent rapidly and or rupture violently. Keep containers and surroundings cool with water spray. Extinguish fire only if gas flow can be stopped. If possible, shut off the source of gas and allow the fire to burn itself out. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. Move away from container and cool with water from a protected position. Keep adjacent cylinders cool by spraying with large amounts of water until fire burns itself out. If flames are accidentally extinguished, explosive re-ignition may occur; therefore, appropriate measures should be taken (e.g. total evacuation to protect persons from cylinder fragments and toxic fumes should a rupture occur).

5.3 Advice for firefighters:

In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate personnel to safe areas. Remove all sources of ignition. Never enter a confined space or other area where the flammable gas concentration is greater the 10% of its lower flammable limit. Ventilate the area.

6.2 Environmental precautions:

Do not discharge into any place where its accumulation could be dangerous. Should not be released into the environment. Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up:

Ventilate the area. Approach suspected leak areas with caution.

Additional advice: Increase ventilation to the release area and monitor concentrations. If leak is from cylinder or cylinder valve, call the emergency telephone number. If the leak is in the user's system, close the cylinder valve,

safely vent the pressure, and purge with an inert gas before attempting repairs.

6.4 Reference to other sections: For more information refer to Sections 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling: Acetylene cylinders are heavier than other cylinders because they are packed with a porous filler material and acetone or dimethylformamide. Never use acetylene in excess of 15 psig pressure. Ensure adequate ventilation. Solvent may accumulate in piping systems. For maintenance activities use appropriate resistant gloves, assess the necessity to use a respiratory filter device (specify gloves and filters for DMF or acetone use), and wear safety goggles. Avoid breathing the vapour of the solvent. Provide adequate ventilation. Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C (122°F). Only experienced and properly instructed persons should handle compressed gases/cryogenic liquids. Before using the product, determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Use an adjustable strap wrench to remove over-tight or rusted caps. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction. Ensure the complete gas system has been checked for leaks before use. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing a leak to occur. Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Close valve after each use and when empty. Replace outlet caps or plugs and container caps as soon as container is disconnected from equipment. Do not subject containers to abnormal mechanical shock. Never attempt to lift a cylinder by its valve protection cap or guard. Do not use containers as rollers or supports or for any other purpose than to contain the gas as supplied. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit. Do not smoke while handling product or cylinders. Never re-compress a gas or a gas mixture without first consulting the supplier. Never attempt to transfer gases from one cylinder/container to another. Always use back flow protective device in piping. Purge air from system before introducing gas. When returning cylinder install valve outlet cap or plug leak tight. Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C (122°F). Ensure equipment is adequately earthed.

7.2 Conditions for safe storage, including any incompatibilities: Containers should be stored in a purpose build compound which should be well ventilated, preferably in the open air. Observe all regulations and local requirements regarding storage of containers. Stored containers should be periodically checked for general condition and leakage. Protect containers stored in the open against rusting and extremes of weather. Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged. Container valve guards or caps should be in place. Keep containers tightly closed in a cool, well-ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Full and empty cylinders should be segregated. Do not allow storage temperature to exceed 50°C (122°F). Smoking should be prohibited within storage areas or while handling product or containers. Display "No Smoking or Open Flames" signs in the storage areas. The amounts of flammable or toxic gases in storage should be kept to a minimum. Return empty containers in a timely manner.

Technical measures/
precautions:

Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) and in accordance with local regulations. Keep away from combustible material. All electrical equipment in the storage areas should be compatible with flammable materials stored. Containers containing flammable gases should be stored away from other combustible materials. Where necessary containers containing oxygen and oxidants should be separated from flammable gases by a fire resistant partition.

7.3 Specific end use(s): Refer to section 1 or the extended MSDS if applicable.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters: If applicable, refer to the extended section of the MSDS for further information on CSA.

DNEL: Derived no effect level (Workers)

Acute - systemic effects, inhalation: 2675 mg/m³

Long-term - systemic effects, inhalation: 2675 mg/m³

PNEC: predicted no effect concentration: None established.

8.2 Exposure controls

Engineering measures: Provide natural or explosion-proof ventilation that is adequate to ensure flammable gas does not reach its lower explosive limit.

Personal Protective Equipment

Respiratory protection: High concentrations that can cause rapid suffocation are within the flammable range and should not be entered.

Hand protection: Wear work gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk.

Eye and face protection: Safety glasses recommended when handling cylinders.
Standard EN 166 - Personal eye-protection.

Skin and body protection: Consider the use of flame resistant anti-static safety clothing.
Standard EN ISO 14116 - Limited flame spread materials.
Standard EN ISO 1149-5 - Protective clothing: Electrostatic properties.
Safety shoes are recommended when handling cylinders.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

Special instructions for protection and hygiene: Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls: If applicable, refer to the extended section of the MSDS for further information on CSA.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

(A/B) Physical state/colour: Dissolved gas. Colourless gas.

(C) Odour: Garlic-like. Poor warning properties at low concentrations.

(D) Density: 0.0011 g/cm³ (0.069 lb/ft³) at 21 °C (70 °F)
Note: (as vapour)

(E) Relative density: Not applicable.

(F) Melting point/freezing point: -113 °F (-80.8 °C)

(G) Boiling point/range:	-120 °F (-84.7 °C)
(H) Vapour pressure:	638.14 psia (44.00 bara) at 68 °F (20 °C)
(I) Water solubility:	1.185 g/l
(J) Partition coefficient: n-octanol/water [log kow]	0.37
(K) pH:	Not applicable for gases and gas mixtures.
(L) Viscosity:	Not reliable data available.
(M) Particle characteristics:	Not applicable for gases and gas mixtures.
(N) Upper and lower explosion/ flammability limits:	100%(V) / 2.3%(V)
(O) Flash point:	Not applicable for gases and gas mixtures.
(P) Autoignition temperature:	305 °C
(Q) Decomposition temperature:	780 °C

9.2 Other information

Explosive properties:	Not applicable.
Oxidizing properties:	Not applicable.
Molecular weight:	26 g/mol.
Odour threshold:	Odour threshold is subjective and inadequate to warn of overexposure.
Evaporation rate:	Not applicable for gases and gas mixtures.
Flammability (solid, gas):	Refer to product classification in section 2.
Specific volume:	0.9221 m ³ /kg (14.77 ft ³ /lb) at 21 °C (70 °F)
Relative vapour density:	0.899 (air = 1) Lighter or similar to air.

SECTION 10: Stability and reactivity

- 10.1 Reactivity:** No reactive hazard other than the effects described in sub-sections below.
- 10.2 Chemical stability:** Stable under normal conditions.
- 10.3 Possibility of hazardous reactions:** Unstable. Stable as shipped. Do not use at pressure above 15 psig.
- 10.4 Conditions to avoid:** Cylinders should not be exposed to sudden shock or sources of heat. Heat, flames and sparks. May form explosive mixtures with air and oxidizing agents.
- 10.5 Incompatible materials:** Under certain conditions, acetylene can react with copper, silver, and mercury to form acetylides, compounds which can act as ignition sources. Brasses containing less than 65% copper in the alloy and certain nickel alloys are suitable for acetylene service under normal conditions. Acetylene can react explosively when combined with oxygen and other oxidizers including all halogens and halogen compounds. The presence of moisture, certain acids, or alkaline materials tends to enhance the formation of copper acetylides.
Oxygen.

Oxidizing agents.

10.6 Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Likely routes of exposure

Effects on eye:	In case of direct contact with eyes, seek medical advice.
Effects on skin:	Adverse effects not expected from this product.
Inhalation effects:	May cause anaesthetic effects. In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Asphyxiation may bring about unconsciousness without warning and so rapidly that victim may be unable to protect themselves.
Ingestion effects:	Ingestion is not considered a potential route of exposure.
Symptoms:	Exposure to oxygen deficient atmosphere may cause the following symptoms: Dizziness. Salivation. Nausea. Vomiting. Loss of mobility/consciousness.

Acute toxicity

Acute oral toxicity:	No data is available on the product itself.
Acute inhalation toxicity:	No data is available on the product itself.
Acute dermal toxicity:	No data is available on the product itself.
Skin corrosion/irritation:	No data available.
Serious eye damage/eye irritation:	No data available.
Sensitisation:	No data available.

Chronic toxicity or effects from long term exposures

Carcinogenicity:	No data available.
Reproductive toxicity:	No data is available on the product itself.
Germ cell mutagenicity:	No data is available on the product itself.
Specific target organ systemic toxicity (single exposure):	No data available.
Specific target organ systemic toxicity (repeated exposure):	No data available.
Aspiration hazard:	No data available.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

LC50 (96h): 545 mg/l	Species: Fish
EC50 (48h): 242 mg/l	Species: Daphnia magna
EC50 (72h): 57 mg/l	Species: Algae

Toxicity to other organisms: No data is available on the product itself.

12.2 Persistence and degradability: No data available.

12.3 Bioaccumulative potential: No data is available on the product itself.

12.4 Mobility in soil: Not data available.

12.5 Results of PBT and vPvB assessment: If applicable, refer to the extended section of the MSDS for further information on CSA.

12.6 Other adverse effects: This product has no known eco-toxicological effects.

Effects on the ozone layer: No known effects from this product.

Ozone depleting potential: None.

Effect on global warming: When discharged in large quantities may contribute to the greenhouse effect.

Global warming potential: None

SECTION 13: Disposal considerations

13.1 Waste treatment methods: Contact supplier if guidance is required. Return unused product in original cylinder to supplier. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Refer to the EIGA code of practice Doc. 30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods. List of hazardous waste codes: 16 05 04*: gases in pressure containers (including halons) containing hazardous substances.

Contaminated packaging: Return cylinder to supplier.

SECTION 14: Transport information

14.1 UN number

UN/ID No. UN1001

14.2 UN proper shipping name

Transport by road/rail (ADR/RID): ACETYLENE, DISSOLVED

Transport by air (ICAO-TI/IATA-DGR): ACETYLENE, DISSOLVED

Transport by sea (IMDG): ACETYLENE, DISSOLVED

14.3 Transport hazard class/es

Label(s): 2.1

Transport by road/rail (ADR/RID)

Class or division: 2
ADR/RID hazard ID no.: 239
Tunnel code: (B/D)

Transport by air (ICAO-TI/IATA-DGR)

Class or division: 2.1

Transport by sea (IMDG)

Class or division: 2.1

14.4 Packing group

Transport by road/rail (ADR/RID): Not applicable.
Transport by air (ICAO-TI/IATA-DGR): Not applicable.
Transport by sea (IMDG): Not applicable.

14.5 Environmental hazards

Transport by road/rail (ADR/RID)

Marine pollutant: No.

Transport by air (ICAO-TI/IATA-DGR)

Marine pollutant: No.

Transport by sea (IMDG)

Marine pollutant: No.

Segregation group: None.

14.6 Special precautions for user

Transport by air (ICAO-TI/IATA-DGR)

Passenger and cargo aircraft: Transport forbidden.

Cargo aircraft only: Transport allowed.

Further information: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact customer service.

14.7 Transport in bulk according to Annex II of Marpol and the IBC code: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Country	Regulatory list	Notification
USA	TSCA	Included on inventory.
EU	EINECS	Included on inventory.
Canada	DSL	Included on inventory.
Australia	AICS	Included on inventory.
South Korea	ECL	Included on inventory.
China	SEPA	Included on inventory.
Philippines	PICCS	Included on inventory.
Japan	ENCS	Included on inventory.

Other regulations

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Regulation (EC) No 1272/2008 the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 907/2006.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

Health and Safety at Work etc. Act 1974

Management of Health and Safety at Work Regulations (Northern Ireland) 2000 c.388, and as amended

Management of Health and Safety at Work Regulations 1999 (S.I. Number 3242)

The Health and Safety at Work etc. Act 1974 (Application to Environmentally Hazardous Substances) Regulations 2002 (England and Wales and Scotland) 11 March 2002 c.282, and as amended

Health and Safety at Work Order (Application to Environmentally Hazardous Substances) Regulations (Northern Ireland) 2003 (Northern Ireland) 14 March 2003 c52, and as amended

The Control of Major Accident Hazards Regulations 2015 c483

The Control of Major Accident Hazards Regulations (Northern Ireland) 2015 c325

The Pressure Systems Safety Regulations 2000 (S.I. Number 128) link to Pressure Equipment Directive (97/23/EC)

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2011 c1885, and as amended

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations with amendments (Northern Ireland) 2011 c365

The Water Environment (Water Framework Directive) (England and Wales) Regulations 2017 c.407

The Water Environment Regulations (Northern Ireland) 2017 c.81

Pollution Prevention and Control Act 1999 c.24

The Fluorinated Greenhouse Gases Regulations 2015 c.310

The Fluorinated Greenhouse Gases Regulations (Northern Ireland) 2015 c.425
The Acetylene Safety (England and Wales and Scotland) Regulations 2014 c.1639
The Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972 c.917
The Highly Flammable Liquids and Liquefied Petroleum Gases Regulations (Northern Ireland) 1975 c.256
Dangerous Substances and Explosive Atmospheres Regulations (Northern Ireland) 2003 c.152
The Dangerous Substances and Explosive Atmospheres Regulations 2002 c.2776
Pollution Prevention and Control Act 1999
The Environmental Permitting (England and Wales) Regulations 2016
Ozone Depleting Substances Regulations 2015

15.2 Chemical safety assessment: A CSA has been carried out. Applicable EXPOSURE SCENARIOS are available at the following link: www.airproducts.com/esds/74-86-2

SECTION 16: Other information

Ensure all national/local regulations are observed

Hazard statements: H220 Extremely flammable gas.
H230 May react explosively even in the absence of air.
H280 Contains gas under pressure; may explode if heated.

Indication of method: Flammable gases Category 1A Extremely flammable gas. Calculation method.
Chemically unstable gases Category A May react explosively even in the absence of air. Calculation method.
Gases under pressure Dissolved gas Contains gas under pressure; may explode if heated. Calculation method.

Abbreviations and acronyms

ATE Acute Toxicity Estimate.
CLP Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
EINECS European Inventory of Existing Commercial Chemical Substances.
ELINCS European List of Notified Chemical Substances.
CAS# Chemical Abstract Service number.
PPE Personal Protection Equipment.
Kow Octanol-water partition coefficient.
DNEL Derived No Effect Level.
LC50 Lethal Concentration to 50 % of a test population.
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose).

NOEC	No Observed Effect Concentration.
PNEC	Predicted No Effect Concentration.
RMM	Risk Management Measure.
OEL	Occupational Exposure Limit.
PBT	Persistent, Bioaccumulative and Toxic.
vPvB	Very Persistent and Very Bioaccumulative.
STOT	Specific Target Organ Toxicity.
CSA	Chemical Safety Assessment.
EN	European Standard.
UN	United Nations.
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road.
IATA	International Air Transport Association.
IMDG	International Maritime Dangerous Goods.
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail.
WGK	Water Hazard Class.

Key literature references and sources of data

ECHA	Guidance on the compilation of safety data sheets.
ECHA	Guidance on the application of the CLP criteria.
ARIEL database	

Prepared by: **Air Products and Chemicals, Inc. (Global EH&S department)**

For additional information, please visit our product stewardship website at: www.airproducts.com

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws. COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.